

E54E-A

55 years of experience

of an evolving technology. We offer you a professional wash system, designed and created in order to obtain excellent results of cleaning, hygiene and brightness.

High-quality products

conceived by following a policy of energy saving with lower water and detergents consumption.

Top quality and performances

without compromise, all with lower running costs and at a very reasonable price.



Riccio Group Inc.
461 North Service Road West
Unit B38
Oakville, ON L6M 2V5
T: 905.339.5119
F: 1.800.925.1130
sam@ricciogroup.com
www.ricciogroup.com

RICCIO
GROUP

E54E-A

ECOLOGY Dishwasher with Ecoclean Control system to guarantee the partial refill of water at every wash cycle and the guaranteed sanitizing rinse temperature, is the ideal solution in terms of efficacy and hygiene.

TECHNICAL FEATURES

- Control panel with LCD Display
 - EWC System, electronic control with 4 individual programmable cycle
 - Built in Drain pump with Ecology Care system for partial refilling of clean water every washing cycle
 - ETL Sanitation to guarantee a sanitizing wash and a high rinse temperature.
 - Break Tank - AA air gap – built in rinse pump 0.5 HP
 - Adjustable 3 Lt/h detergent dispenser - Adjustable 0,3 Lt/h rinse-aid dispenser
 - Uses standard 20" x 20" (500 x 500 mm) baskets
 - Basket supplied: 1 dish basket, 1 glass basket, 2 cutlery Tray
 - Wash pump: 3/4 HP
 - Tank: heating element: 2.6 kW, capacity: 7 G (26 Lt)
 - Booster: heating element: 2.5 kW, capacity: 1.9 G (7.3 Lt)
 - Door clearance: 15.08" (383 mm) H
 - Stainless steel detergent injector welded to the wash tank
 - Adjustable rotation speed of stainless-steel rinse arms
 - Integral stainless-steel tank filter + New filtering group for suction and drain
 - Low maintenance, heavy duty, Stainless Steel.
 - Warranty 1-year parts and labour, (see details)
- Power requirements: 3.12 kW, 208/220 V, 50/60 Hz, 16 A, 1PH
 - Hot water requirements: ½ GPC (2.6 LPC) 125°F (55°C) (will operate with cold water. At reduced capacity)
 - 40 racks/hour - Approx. 35 racks/hour in accordance to NSF standards
 - Water line requirements: ¾" (or ½" with ¾" NPT terminal) (hose supplied)
 - Drain line: 1" (25 mm) (connection hose supplied)
 - Dimensions: 23 x 24 x 31¾". (585W x 610D x 815H mm)
 - Shipping size: 26¾ x 31½ x 39½". (680W x 800D x 1000H mm)
 - Shipping weight: 153 lbs. (69.2 kg), Net weight 126 lbs (57.5 kg)



Intertek



Intertek

